



Technical Specification

| BS EN 12899:2007 | Clause | Notes |
|----------------------------------|-----------|--------------|
| Deflection | 4.3.1.3 | 0° - 3.67% |
| | | 180° - 7.11% |
| Low impact | 4.3.2.1 | 0° - 0% |
| | | 90° - 0.56% |
| | | 180° - 0.22% |
| | | 270° - 0.33% |
| High impact | 4.3.2.2.3 | 0° - 3.67% |
| Chromaticity & luminance factor: | 4.2.2 | Class B2 |
| Retroreflectivity | 4.2.2 | Class CR2 |
| Mean Luminance | 4.2.3.2.1 | L1 |
| Luminance Contrast | 4.2.3.2.1 | 5.5 |
| Uniformity of Luminance | 4.2.3.2.1 | U2 |
| BS 8442:2015 | Clause | Notes |
| Photometric Performance | 13.2.2 | Compliant |
| Adhesion to Substrate | 13.3.1 | Compliant |
| Corrosion Resistance (Body) | 13.3.2 | SP2 |
| Corrosion Resistance (Fixings) | 13.3.2 | SP1 |

Additional Information

*5 year materials and workmanship warranty
 Passively Safe: Passed in house impact testing at 50Kph
 Made from 100% recyclable materials (excluding retroreflective panels)

Options

Double aspect signage available (rear reflective panels)
 Anti graffiti conspicuity panels available
 Range of fixing options available
 Tamperproof fixing option available on request

* 5 year warranty subject to terms and conditions, contact Pudsey Diamond Engineering for details

Standard sign aspect variants



NOTES: (1) ALL DIMENSIONS IN mm. (2) REMOVE ALL BURRS AND SHARP EDGES.

© 2017 PUDSEY DIAMOND ENGINEERING LTD. ALL RIGHTS RESERVED. THIS DOCUMENT OR ANY PART THEREOF MAY NOT BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY WAY WITHOUT WRITTEN PERMISSION FROM PUDSEY DIAMOND ENGINEERING LTD.

| | | | | | |
|--|--|---|--|------------------------|--|
| LINEAR TOLERANCES UNLESS OTHERWISE STATED: X.00 = ±0.15 X.0 = ±0.50 X = ±5.00 | | ANGULAR TOLERANCES UNLESS OTHERWISE STATED: X.00° = ±0.15° X.0° = ±0.50° X° = ±1.00° | | MATERIAL: SPEC: | |
| DATE: 23/01/15 | | SCALE: | | FINISH: | |
| DRAWN: WH | | CHECKED: | | 3RD ANGLE PROJECTION | |

